

4D 5W LED 50 250



& 5w
 & 2400LM
 & 4D



Picture	Series No.	Size	Specification
	UX-LB5CR-30W	7.4"	. Operating Voltage: 10-30 DC . Waterproof rate: IP 67 . Color Temperature: 6000K . Lens: 4D Lens . Lens material:PC . Material:Diecast aluminum housing . Mounting Bracket: Alu firm bracket . Beam: Flood /spot/combo beam optional . 30000 hours above life time
	UX-LB5CR-50W	11.3"	
	UX-LB5CR-60W	13.3"	
	UX-LB5CR-90W	19.3"	
	UX-LB5CR-100W	21.3"	
	UX-LB5CR-120W	25.4"	
	UX-LB5CR-150W	31.1"	
	UX-LB5CR-180W	37.2"	
	UX-LB5CR-200W	41"	
	UX-LB5CR-210W	43.2"	
	UX-LB5CR-250W	50.9"	











□□□□&□□

About Us

PRODUCTION
WORKSHOP

TEAMWORK

EMBRACE CHANGES

PASSIONATE

DEDICATED



SEMA□□□□



OH MY GOD!



Q1
-

Q2
- Paypal / Western Union / T / DHL

Q3
- 2
3 10
- DHL 3 5

Q4
12



Channy Chen

Tel: +86-20-37026220
Fax: +86-20-87633693

Email: sales09@unionlux.com
Mobile: +86-18127913861
Skype: sales09@unionlux.com
Whatsapp: +86-18127913861
Wechat: Channychen1993