

4D 5W LED 50 250w

□□:

- & 5w
- & : 24000LM
- & 4D

□□ □□ □□ :

Picture	Series No.	Size	Specification
	UX-LB5CR-30W	7.4"	<ul style="list-style-type: none"> . Operating Voltage: 10-30 DC . Waterproof rate: IP 67 . Color Temperature: 6000K . Lens: 4D Lens . Lens material:PC . Material:Diecast aluminum housing . Mounting Bracket: Alu firm bracket . Beam: Flood /spot/combo beam optional . 30000 hours above life time
	UX-LB5CR-50W	11.3"	
	UX-LB5CR-60W	13.3"	
	UX-LB5CR-90W	19.3"	
	UX-LB5CR-100W	21.3"	
	UX-LB5CR-120W	25.4"	
	UX-LB5CR-150W	31.1"	
	UX-LB5CR-180W	37.2"	
	UX-LB5CR-200W	41"	
	UX-LB5CR-210W	43.2"	
	UX-LB5CR-250W	50.9"	











□□ & □□

 PACKAGE		
 SEAFREIGHT		
 AIRFREIGHT		
 PAYMENT		
		

□□□□ □□□□

- & □□□ □□□□□ □□□ □□ □□ □ □□ □□ □□
- & □□□ □ □□ □□ □□ □□ & □□ □□ □□
- & □□□□ □□ □ □□□□ □□□□□□□ □□□ □□.
- & □ □□□, □□ □□ □□□□ □□□ □□□□□□ □□□ □□□ □.
- & □□ □□ □□□ □ □□ □□ □□□□ □□ □□□
- & □□□ □□□ □□ □□□ □□□□□□□ □□ □□ □□.
- & OEM. □□□□ OEM □□ □□□□ □□ □ □ □□□□. □□□□ □□ □□ □□ □□□□□□ □ □ □□□ □□□ □□ (MOQ 500PCS)

□□ □□:

2006 □□ □□ □ Unionlux Lighting □□□ □□ □□□ □□ □□□□□□□□. □□ □□□ HID □□□ □□□ □□□□ □□□□ special. In 2010 □, LED □□□ □□□ □□□ □□ □□□, □□ □□, □□ □□, □□ □□, □□□□ □□□□, LED □□ □□ □□□ □□□□ □□□□□□□□

About Us

PRODUCTION
WORKSHOP

TEAMWORK

EMBRACE CHANGES

PASSIONATE

DEDICATED



SEMA □ :



OH MY GOD!



Q1. 如何 如何 如何 如何 如何?

- 如何 如何 如何 如何 如何 如何, 如何 如何 如何 如何.

Q2. 如何 如何 如何 如何 如何?

- 如何 如何 Paypal, Western Union 如何 T / T如何如何. 如何 如何 如何 如何 如何 如何 如何如何.

Q3. 如何 如何 如何 如何?

- 如何如何 如何 2 如何 如何 如何如何.

- 如何如何 如何 如何 3 ~ 10 如何 如何如何.

- 如何 DHL如何 如何 3 ~ 5 如何 如何如何. 如何 如何 如何 Express如何 如何 如何 如何. 如何

Q4. 如何 如何?

- 如何如何 如何 如何 12 如何如何. 如何 如何 如何 如何如何.

如何:



Channy Chen

Tel: +86-20-37026220
Fax: +86-20-87633693

Email: sales09@unionlux.com
Mobile: +86-18127913861
Skype: sales09@unionlux.com
Whatsapp: +86-18127913861
Wechat: Channychen1993